


## 数字哇音单块 说明书

感谢您使用公司产品，在使用本产品之前请仔细阅读本说明书

### 操作说明



#### 1.直通脚踏开关

- 单踩：效果声与原声切换
- 双踩：固定模式与正常模式切换
- 长踩：储存当前参数

#### 2.LED指示灯

- 绿灯亮：正常模式，可以使用旋钮等调节效果参数
- 红灯亮：固定模式，效果调用预先参数，旋钮等无效
- 灯熄灭：原声输出

#### 3.SPEED旋钮

- 调节效果的速度；

#### 4.RESO旋钮

- 调节效果的共振强度；

#### 5.SPAPE旋钮

- 调节效果的深度；

#### 6.CUTOFF旋钮

- 调节效果的频率变换范围；

#### 7.输入

- 1/4"单声道音频接口，信号输入；

#### 8.输出

- 1/4"单声道音频接口，信号输出；

#### 9.电源接口

- 9V直流电源(外正内负 ⊕ ⊖)；

### 产品特点

- ◆ 采用32位浮点DSP芯片，44.1KHz /24位采样
- ◆ 2种工作模式：正常模式与固定模式，可储存一组参数

### 技术参数

- ◆ 输入：1/4"单声道音接口(阻抗:470k Ohms)
- ◆ 输出：1/4"单声道音接口(阻抗:100 Ohms)
- ◆ 电源供给：9V直流电流(外正内负 ⊕ ⊖)
- ◆ 工作电流：100mA
- ◆ 尺寸：95(L)\*45(W)\*48(H)mm
- ◆ 重量：273克(带包装)

## Auto wah Pedal Manual

Thanks for purchasing our products, before operating this product, please read the enclosed operating instructions.

### Operating Instructions

#### 1.True BYPASS Footswitch

- Press once: Switch between original sound and effect sound
- Press twice: Switch between fixed mode and normal mode
- Longtime Press : Store the current parameters.

#### 2.LED indicator light

- Green light: Normal mode, can use knob to adjust parameters
- Red light: Fixed mode,effector use the fixed parameter, knob can't be use
- Go out: Original sound

#### 3.SPEED Knob

- Adjust the speed.

#### 4.RESO Knob

- Adjusts the intensity of resonance.

#### 5.SPAPE Knob

- Adjusts the wah depth.

#### 6.CUTOFF Knob

- Adjusts the frequency range of wah effects.

#### 7.Input Jack

- 1/4"mono audio jack,inputs the signal.

#### 8.Output Jack

- 1/4"mono audio jack,outputs the signal.

#### 9.DC IN Power Jack

- DC 9V regulated AC adapter (Plug polarity is Positive on the barrel and negative in the center ⊕ ⊖)

### Product features

- ◆ DSP: 32 bit floating point, Sampling: 44.1kHz/ 24bit.
- ◆ 2 Models ( Normal mode and fixed mode), can store a set of parameters.

### Specifications

- ◆ Input: 1/4" Monaural Jack (Impedance: 470K Ohms)
- ◆ Output: 1/4" Monaural Jack (Impedance: 100 Ohms)
- ◆ Power Supply: DC 9V (Plug polarity is Positive on the barrel and negative in the center ⊕ ⊖)
- ◆ Working Current: 100mA
- ◆ Dimensions: 95(D)\*45(W)\*48(H)mm
- ◆ Weight: 273g(With box)

尺寸：170\*120 mm  
正反面，边框线不要印